

2/19/27

DIALOG(R)File 347:JAPIO

(c) 2003 JPO & JAPIO. All rts. reserv.

05383034 **Image available**
SEALING DEVICE

PUB. NO.: 08-338534 [JP 8338534 A]
PUBLISHED: December 24, 1996 (19961224)
INVENTOR(s): SHIRAKI TOSHIHIKO
 WAKABAYASHI MITSURU
APPLICANT(s): KOYO SEIKO CO LTD [000124] (A Japanese Company or
 Corporation), JP (Japan)
 TOYO SEAL KOGYO KK [458543] (A Japanese Company or
 Corporation), JP (Japan)
APPL. NO.: 07-169275 [JP 95169275]
FILED: June 12, 1995 (19950612)
INTL CLASS: [6] F16J-015/32 ; F04D-029/12
JAPIO CLASS: 22.1 (MACHINERY -- Machine Elements); 24.1 (CHEMICAL
 ENGINEERING -- Fluid Transportation); 26.2 (TRANSPORTATION --
 Motor Vehicles)

ABSTRACT

PURPOSE: To facilitate assembling of an outer lip and obtain stable sealability in a device which makes a lip of a seal body be in sliding contact with a slinger fixed to a rotational member for sealing between an unrotational member and the rotational member by so setting a measurement of an inner diameter of the outer lip as to be without contact or in linear contact with the slinger.

CONSTITUTION: A sealing device of a water pump **bearing** for an automobile has a slinger 4 composed of a flange 5 and a cylindrical part 6 fitted and fixed to a pump **shaft** 1. The cylindrical part 6 is composed of a small diameter cylindrical part 6a closely fitted to the pump **shaft** 1, and a large diameter cylindrical part 6b arranged substantially parallelly to the small diameter cylindrical part 6a without contact to the pump **shaft** 1, and a tapered stepped portion 6c therebetween. A **seal** body 7 is arranged between the slinger 4 and a **bearing** outer ring 2. An inner **lip** 7a tapered inward is in sliding contact with the small diameter cylindrical part 6a, while an outer **lip** 7b which is tapered outward without contact or in linear contact to the small diameter cylindrical part 6a is in sliding contact with the large diameter cylindrical part 6b, respectively with specified fastening margins.

C:\Program Files\Dialog\DialogLink\Graphics\1F.bmp

